Datenblatt - Fiche technique - Data sheet

21.19.7301

ROLINE 3 MPx Fix Bullet IP Camera

ROLINE 3 MPx Fix Bullet IP Camera

ROLINE 3 MPx Fix Bullet IP Camera

roline®
Designed for Professionals

ROLINE 3 MPx Fix Bullet IP Camera

RBOF3-1

Features:

- Up to 3 megapixel 2048×1536 @ 20 fps resolution
- Angle of view: 70°(4mm lens)
- 3D DNR & DWDR & BLC
- Standard video compression with high compression ratio
- Progressive scan CMOS
- Support dual stream, and the sub-stream for mobile surveillance
- Bulit-in IR Illuminators up to 30 meters
- Removable IR-cut Filter with auto switch for Day & Night Function
- PoE (Power over Ethernet) 802.3af
- Weather-proof IP66 rated housing
- Electronic shutter for different surveillance environments
- Other functions: alarm, reset button, mirror, etc.
- Compact design, Built-in bracket

roline®
Designed for Professionals

Specification:

Parameter \ Model	21.19.7301 – RBOF3-1
	3 Megapixel CMOS ICR Infrared Network Bullet Camera
Camera	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	0.07Lux @ (F1.2, AGC ON) ,0 Lux with IR
Shutter Speed	1/25(1/30) s to 1/100,000 s
Lens	4mm@ F2.0
	2048 × 1536: Angle of view: 70°(4mm) 1920 × 1080: Angle of view: 79°(4mm)
Lens Mount	M12
Day &Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Compression Standard	
Video Compression	H.264/ MJPEG
Video Bit Rate	32 Kbps – 12 Mbps
Dual Stream	Yes
Image	
Max. Resolution	2048×1536
Frame Rate	50Hz: 20fps (2048 × 1536), 25fps (1920 × 1080), 25fps (1280 × 720) 60Hz: 20fps (2048 × 1536), 30fps (1920 × 1080), 30fps (1280 × 720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone optional
ROI	Yes, up to 3 configurable areas
Network	
Network Storage	NAS
Alarm Trigger	Motion detection, Dynamic analysis, Tampering alarm
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour(SIP optional)
Security	User Authentication, Watermark
Standard	ONVIF, PSIA, CGI, ISAPI
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet interface
Reset Button	Yes
General	
Operating Conditions	-30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 10% PoE (802.3af)
Power Consumption	Max. 5 W (Max. 7 W with IR cut filter on)
Ingress Protection level	IP66
IR Range	Approx. 20 to 30 meters
Dimensions	62.0 × 62.0 × 162.54 mm (2.4” × 2.4” × 6.4”)
Weight	500g (1.1 lbs)

Dimension: